



AQUA LOGIC HEAT EXCHANGERS

| MODEL # | NOMINAL HP | *NOMINAL BTUH/KW | A | B | WATER FLOW RATE MIN/MAX. (GPM) | WATER CONNECTION INLET/OUTLET (INCH) | REFRIGERANT CONNECTION HIGH/LOW (ODF) |
|---------|------------|------------------|-----|-----|--------------------------------|--------------------------------------|---------------------------------------|
| HX-2DX | 1/5 | 1,800/.5 | 12" | 20" | 6/12 | 3/4 | 3/8 / 3/8 |
| HX-3DX | 1/4 | 3,000/.8 | 12" | 20" | 8/15 | 3/4 | 3/8 / 3/8 |
| HX-4DX | 1/3 | 4,000/1.2 | 12" | 22" | 10/20 | 3/4 | 3/8 / 3/8 |
| HX-6DX | 1/2 | 6,000/1.8 | 12" | 23" | 12/25 | 1 1/2 | 3/8 / 1/2 |
| HX-9DX | 3/4 | 9,500/2.6 | 16" | 30" | 20/35 | 1 1/2 | 3/8 / 1/2 |
| HX-12DX | 1 | 12,000/3.5 | 16" | 33" | 25/40 | 1 1/2 | 3/8 / 5/8 |

aqualogic
 Aqua Logic, Inc.
 8268 Clairemont Mesa Blvd. Suite 302
 San Diego, CA 92111

TITLE: HX-3DX thru HX-12DX
 Specifications, 24V
 Control