



CHILLER SPECIFICATIONS

MODEL NO.	HP / TONS	NOMINAL BTUH / KW	VOLTS / PHASE	AMPS.	WATTS	L	W	H	W2	WO	WI	R134A REFRIGERANT CHARGE (OZ.)	AIR OUTPUT (CFM)	WC WATER IN/OUT (FPT)	WATER FLOW RATE (GPM)	WEIGHT (LBS.)	SHIPPING WEIGHT (LBS.)	SHIPPING DIMENSIONS (INCHES)
DSHP-4	1/3	4,050 / 1.1	115	7.2	828	22 1/2"	13"	14"	2"	7 1/2"	3 1/2"	8.5	260	3/4	10-20	80	90	29x18x16
DSHP-5	1/2	6,000 / 1.75	115	9.5	1092	24"	15 1/2"	13"	3"	9"	4"	10	350	1 1/2	12-25	115	135	33x26x25
DSHP-6	1/2	6,000 / 1.75	230/1	4.8	1104	24"	15 1/2"	13"	3"	9"	4"	10	350	1 1/2	12-25	115	135	33x26x25

NOTE: DO NOT OPERATE IN HEAT MODE BELOW 55°F AIR TEMPERATURE
 ALL DIMENSIONS ARE APPROXIMATE AND CAN CHANGE WITHOUT NOTICE

WI=WATER INLET
 WO=WATER OUTLET
 WC=WATER CONNECTION SIZE

LAST UPDATE: 10-26-06	DATE: 10-26-06	FILE: DSHP-4, 5 & 6 SPEC	BY: CE
-----------------------	----------------	--------------------------	--------

AquaLogic
 Aqua Logic, Inc.
 8288 Clairemont Mesa Blvd. Suite 302
 San Diego, CA 92111

TITLE: DSHP-4 THRU DSHP-6
 HEAT PUMP SPECIFICATIONS