



WATER-COOLED DELTA STAR HEAT PUMP SPECIFICATIONS

MODEL NO.	HP/TONS	NOMINAL BTUH	VOLTS / PHASE	AMPS.	WATTS	L	W	H	W2	WO	WI	R134A REFRIGERANT CHARGE (OZ.)	*CITY WATER USE (GPM)	WC WATER IN/OUT (FPT)	WATER FLOW RATE (GPM)	WEIGHT (LBS.)	SHIPPING WEIGHT (LBS.)	SHIPPING DIMENSIONS (INCHES)
DSHP-4WC	1/3	4,050	115	7.2	828	22 1/2"	13"	11"	2"	7 1/2"	3 1/2"	8	.5	3/4	10-20	66	69	29x18x16
DSHP-5WC	1/2	6,000	115	9.5	1092	24"	15 1/2"	13"	3"	9"	4"	9.5	.7	1 1/2	12-25	100	119	33x26x25
DSHP-6WC	1/2	6,000	230/1	4.8	1104	24"	15 1/2"	13"	3"	9"	4"	9.5	.7	1 1/2	12-25	100	119	33x26x25

* CITY WATER USE BASED ON 55-60°F WATER TEMPERATURE ENTERING THE UNIT. WATER FLOWS THROUGH UNIT ONLY WHEN THE UNIT IS RUNNING

ALL DIMENSIONS ARE APPROXIMATE AND CAN CHANGE WITHOUT NOTICE

AQUALOGIC
Aqua Logic, Inc.
8288 Clairemont Mesa Blvd. Suite 302
San Diego, CA 92111

TITLE: DSHP-4WC THRU DSHP-6WC
WATER-COOLED DELTA STAR HEAT
PUMP SPECIFICATIONS