



CHILLER SPECIFICATIONS

MODEL NO.	HP/TONS	NOMINAL BTUH/KW	VOLTS / PHASE	AMPS.	WATTS	L	W	H	WO	REFRIGERANT TYPE/CHARGE	WATER FLOW RATE (GPM)	AIR OUTPUT (CFM)	WEIGHT (LBS.)	SHIPPING WEIGHT (LBS.)	SHIPPING DIMENSIONS (INCHES)
DSHP-7	3/4	9500 / 2.7	115	13	1495	25"	21"	15"	9"	R134A / 3 Lbs.	15-30	590	135	170	33x26x23
DSHP-8	3/4	9500 / 2.7	230/1	7	1610	25"	21"	15"	9"	R134A / 3 Lbs.	15-30	590	135	170	33x26x23
DSHP-9	1	12,000 / 3.4	230/1	7.2	1656	27"	24"	15"	9"	R134A / 3.5 Lbs.	20-35	610	140	180	33x26x23
DSHP-10	1 1/2	21,000 / 6.1	230/1	10.5	2415	31"	26"	19"	12"	R22 / 4.5 Lbs.	25-40	772	160	225	36x33x24

ALL DIMENSIONS ARE APPROXIMATE AND CAN CHANGE WITHOUT NOTICE  
 NOTE: DO NOT OPERATE IN HEAT MODE BELOW 55°F AIR TEMPERATURE

LAST UPDATE: 10-26-06 DATE: 10-26-06 FILE: DSHP-7, 8, 9 & 10 SPEC BY: CE

**AquaLogic**  
 AquaLogic, Inc.  
 8268 Clairemont Mesa Blvd. Suite 302  
 San Diego, CA 92111

TITLE: DSHP-7 THUR DSHP-10  
 HEAT PUMP  
 SPECIFICATIONS