



WATER-COOLED DELTA STAR HEAT PUMP SPECIFICATIONS

MODEL NO.	HP/TONS	NOMINAL BTUH	VOLTS / PHASE	AMPS.	WATTS	L	W	H	WO	REFRIGERANT TYPE/CHARGE	*CITY WATER USE (GPM)	AIR OUTPUT (CFM)	WEIGHT (LBS.)	SHIPPING WEIGHT (LBS.)	SHIPPING DIMENSIONS (INCHES)
DSHP-7WC	3/4	9500	115	13	1495	25"	21"	15"	9"	R134A / 2 Lbs. 6 oz	1	590	112	150	33x26x23
DSHP-8WC	3/4	9500	230/1	7	1610	25"	21"	15"	9"	R134A / 2 Lbs. 6 oz	1	590	112	150	33x26x23
DSHP-9WC	1	12,000	230/1	7.2	1656	27"	24"	15"	9"	R134A / 3 Lbs.	1.5	610	117	160	33x26x23
DSHP-10WC	1 1/2	21,000	230/1	10.5	2415	31"	26"	19"	12"	R22 / 4 Lbs.	2	772	147	250	36x33x24

* CITY WATER USE BASED ON 55-60°F WATER TEMPERATURE ENTERING THE UNIT. WATER FLOWS THROUGH UNIT ONLY WHEN THE UNIT IS RUNNING

ALL DIMENSIONS ARE APPROXIMATE AND CAN CHANGE WITHOUT NOTICE

Aqua Logic, Inc.
8268 Clairemont Mesa Blvd. Suite 302
San Diego, CA 92111

TITLE: DSHP-7WC THUR DSHP-10WC
WATER-COOLED DELTA STAR HEAT
PUMP SPECIFICATIONS

LAST UPDATE: 2-11-08	DATE: 2-9-06	FILE: DSHP-7,8,9 & 10WC SPEC
		BY CE